



MARINE CASSETTE LAUTEX WL-600





- ① = WL-600; unperforated without acoustic inlay
 ② = WLT-600; unperforated. with mineral wool in plastic
 ③ = NL-600; fitting cassette NL-600 (0.7 Al)



WL-600 CASSETTES / CLASSIFICATION "C"

Material	0.5 Steel
Module	600x600 mm
Height	25 mm
Perforation	none
Inlay	mineral wool in plastic
Finish	NCS S or RAL color
Protective film	the surface is provided with a protective film if required
Loudspeaker	perforated cassette with $\varnothing 3.5/25\%$, area 260x260
Edge lists	see "Lautex lists" and "Lautex marine cassettes typical details"
Suspensions	see "Suspensions systems for L-type cassettes"
Other solutions	please contact Lautex sales

MARINE CASSETTE LAUTEX WL-600 INSTALLATION ACCESSORIES



CASSETTE CONNECTION TO WALL PLEASE SEE PAGE 21

THEORETICAL NEED OF SUSPENSION STRUCTURES

Product	Need of material
Carrier No. 42	1.8 m/m ²
L-list No. 50	0.8 – 1.4 m/m ²
Z-list No. 51C	0.8 – 1.4 m/m ²

WEIGHT OF CEILING

Cassette	WL-600
Material	0.5 Steel
Weight	4.6 Kg/m ²

WEIGHT OF OTHER CEILING MATERIALS

Product	Weight of material
Carrier No. 42 (1.0 Steel)	0.83 kg/m
L-list No. 50 or 83 (1.5 Al)	0.32 kg/m
L-list No. 50 or 83 (1.0 steel)	0.62 kg/m
Z-list No. 51C (1.0 Al)	0.16 kg/m
Mineral wool in plastic	0.52 kg/m ²